

TECHNICAL DATA SHEET

Sparco Series



Stain Proof Aqua Matt Finish



Packing Size

0.91, 3.64, 14.56 Ltr

Handling

Handle with care. stir well before use

Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Health and Safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately. For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

Typical Paint System

Sparco Water based Primer	1-2 Coats
Sparco Wall Putty	2-3 Coats
Sparco Stain Proof	2-3 Coats

Product Description

Sparco stain proof is a premium interior wall paint which is a striking combination of luxury & durable Silk finish. This luxurious finish is designed to be easy to clean, it prevents stain penetration into the paint film, Due to its high wash ability, walls stay beautiful for longer last.

Recommended Use

Most suitable for internal use on cement plastered walls, ceilings, concrete, rendered block work, gypsum board partitions etc. It is perfect for high traffic areas such as hallways and kid's room.

Film thickness and Spreading Rate

Dry film thickness	25-35 μ
Wet film thickness	60-70 μ
Theoretical Spreading Rate	14-16 m ² / Litre / Coat

Physical properties

Colour	As per Shade Card
Finish	Matt
Volume solids	40 3
Flash Point	N.A
Specific Gravity	1.35-1.45

Surface Preparation

The substrate must be sound, clean, dry, free from dust, oil and grease etc. it can be either pre-primed or smooth surface. All traces of release agents must be removed. On chalky and dusty surfaces, all loose material must be removed by stiff bristle brushing.

Application methods



Drying Time

Temperature	Touch Dry	Recoating Interval	Hard Dry
23°C	40 min	4 hours	6 Hours
30°C	30 min	3 hours	4 hours
38°C	20 min	2 hours	2 Hours

Application Data

System	Single component System
Thinner	Clean Water
Thinning Ratio %	20-40 %

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product can be used under conditions beyond our control, we can only guarantee the quality of the product itself. We also reserve the right to change the given data without notice.