

## PU Hardener



### Packing Size

0.5 Litre

### Handling

Handle with care, stir well before use

### Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

### Health and Safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately. For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

### Product Description

Sparco PU Hardener is used primarily as the hardener component for light fast two-component polyurethane coatings with high resistance to chemicals and weathering, very good gloss retention and outstanding mechanical properties. Preferred co-reactants are polyacrylate or polyester polyols.

### Recommended use

The main applications for systems based on Sparco PU Hardener are air- and force-drying coatings for automotive OEM, automotive refinishing, transportation, industrial finishing and plastics.

### Physical properties

Color	Water White
Finish	Hard Glossy
Flash Point	10 °C
Specific Gravity	0.85-0.95

System	Two Component System
Lacquer Hardener Mixing Ratio	PU Clear Coat : Hardener - 2:1
Thinner	Sparco 2K Thinner
Thinning Ratio	30-40 %

#### DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product can be used under conditions beyond our control, we can only guarantee the quality of the product itself. We also reserve the right to change the given data without notice.